



## Preventive Maintenance – Spray Equipment Lathe Without Traverse

<b>Preventive Action</b>	<b>Safety Inspection</b>	<b>Basic Service Contract</b>	<b>Upgraded Service Contract</b>
Service Interruption	Minimal	Medium	Full planned outage
Headstock:			
Lubricate bearings		X	X
Check motors for spin speed	X	X	X
Check wear of pulleys and belt		X	
Replace pulleys and belt			X
Chuck run out and adjust			X
Concentricity and adjust			X
Inspect dead center	X	X	X
Inspect position of safety cover	X	X	X
Check RPM pickup		X	X
Adjust gearbox oil level			X
Tailstock:			
Check condition of live center	X	X	X
Inspect air valve and cylinder	X	X	X
Inspect air regulator & gauge	X	X	X
Inspect air lines for leakage	X	X	X
Add hydraulic pump oil			X
Check hydraulic cylinders		X	X
Check hydraulic lines	X	X	X
Check gauge for functionality		X	X
Inspect rollers and CAMS	X	X	X
Bed:			
Check centerline alignment		X	X
Check top surface for tail stk.	X	X	X
Inspect leveling bolts	X	X	X
Inspect floor anchors	X	X	X
Inspect connectors	X	X	X



**Preventative Maintenance – Spray Equipment Lathe Without Traverse**

<b>Preventive Action</b>	<b>Safety Inspection</b>	<b>Basic Service Contract</b>	<b>Upgraded Service Contract</b>
Service Interruption	Minimal	Medium	Full planned outage
Control panel:			
Check safety circuits		X	X
Clean VFD		X	X
Clean cooling fan		X	X
Check intake fan	X	X	X
Inspect RPM display	X	X	X
Check local & remote controls		X	X
Inspect terminal tightness			X
Test incoming power		X	X
Test control power (VDC or VAC)		X	X
Test amp draw for lathe		X	X

Note: Additional charges will apply if travel time to facility is greater than one hour from Arzell, Inc.