

Preventive Maintenance – Spray Equipment Lathe

Preventive Action	Safety Inspection	Basic Service Contract	Upgraded Service Contract
Service Interruption	Minimal	Medium	Full planned
·			outage
			¥
Headstock:			
Lubricate bearings		Х	Х
Check motors for spin speed	Х	Х	Х
Check wear of pulleys and belt		Х	
Replace pulleys and belt			Х
Chuck run out and adjust			Х
Concentricity and adjust			Х
Inspect dead center	Х	Х	Х
Inspect position of safety cover	Х	Х	Х
Check RPM pickup		Х	Х
Adjust gearbox oil level			Х
Tailstock:			
Check condition of live center	Х	Х	Х
Inspect air valve and cylinder	Х	Х	Х
Inspect air regulator & gauge	Х	Х	Х
Inspect air lines for leakage	Х	Х	Х
Add hydraulic pump oil			Х
Check hydraulic cylinders		Х	Х
Check hydraulic lines	Х	Х	Х
Check gauge for functionality		Х	Х
Inspect rollers and CAMS	Х	Х	Х
Traverse:			
Check V-groove rollers	Х	Х	Х
Adjust gearbox oil level			Х
Adjust gearbox mount plate			Х
Check gear rack and pinion	X X	Х	Х
Check limit switches		Х	Х
Check traverse play	Х	Х	Х
Check air valve for leakage	Х	Х	Х
Check air cylinder	Х	Х	Х



Preventative Maintenance – Spray Equipment Lathe

Preventive Action	Safety Inspection	Basic Service Contract	Upgraded Service Contract
Service Interruption	Minimal	Medium	Full planned
			outage
Traverse (continued)			
Check air regulators	Х	Х	Х
Check air gauge and lines	Х	Х	Х
Check torch actuator play	Х	Х	Х
Bed:			
Check centerline alignment		Х	Х
Check top surface for tail stk.	Х	Х	Х
Inspect leveling bolts	Х	Х	Х
Inspect floor anchors	Х	Х	Х
Check flex chains and cables	Х	Х	Х
Inspect connectors	Х	Х	Х
Control panel:			
Check safety circuits		Х	Х
Clean VFD		Х	Х
Clean cooling fan		Х	Х
Check intake fan	Х	Х	Х
Inspect RPM display	Х	Х	Х
Check local & remote controls		Х	Х
Inspect terminal tightness			Х
Test incoming power		Х	Х
Test control power (VDC or VAC)		Х	Х
Test amp draw for lathe		Х	Х
Test amp draw for traverse		Х	Х

<u>Note</u>: Additional charges will apply if travel time to facility is greater than one hour from Arzell, Inc.